MODEL SPECIFICATION

# E25145(115-0500x0600-L212) – Prep Table, Slatted Shelf 500 mm x 600 mm

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | E25145(115-0500x0600-L212){PSS} | 21 Nov 2026 |

## 01 Model specification

Grade 304 Stainless Steel Preparation Table, 500 mm (L) x 600 mm (W) x 900 mm (H). Worktop Thickness: 1.5 mm. Undershelf: Slatted Grade 430 1.2 mm. Stainless Steel Frame and Legs with Adjustable Stainless Steel Feet.

Height Specification: 900 mm Working Height (900 mm Overall), Without a Splashback.

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Working Height** | 900 | mm | 900 mm standard; 850 mm or 1000 mm through advanced customisation. |
| **Overall height** | 900 | mm | Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height. |
| **Material** | Stainless Steel Grade 304 | – | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| **Length** | 500 | mm | The length of the item typically as measured from left to right. |
| **Width** | 600 | mm | The width of the item typically as measured from front to back. |
| **Material Thickness** | 1.5 | mm | Grade 304 worktop: fixed at 1.5 mm for E25145(115). |


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Undershelf** | Slatted Grade 430 1.2 mm | – | Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration. |

## 03 Dimensions and mass

| PARAMETER | VALUE | UNIT |
|---|---|---|
| **Overall height** | 900 | mm |

## 04 Model and supply data

| | |
|---|---|
| **Parent product** | E25145(115) — Grade 304 Heavy Duty Preparation Table (1.5 mm) |
| **Typical lead time** | 10–15 working days |
| **Warranty** | 24 months |

## 05 Frequently asked questions

**Which worktop thickness belongs to this range?**

E25145(115) has a fixed 1.5 mm Grade 304 worktop. Other worktop thicknesses have separate product ranges.

**What is the standard working height?**

The standard working height is 900 mm.

**Which undershelf options are available?**

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

**Which sizes are available?**

Lengths: 500, 900, 1200, 1500, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Select the required length, width and undershelf specification in the configurator.

**Which advanced options are available?**

Advanced working heights are 850 mm and 1000 mm. Working height equals overall height because no splashback is fitted.

**What supports the worktop?**

A stainless steel sub-frame supports the worktop, with no timber or galvanised backing beneath it.

E&OE. Specifications are subject to change without notice.