

MODEL SPECIFICATION

E25145(120-0500x0600-P112) – Prep Table, Perforated Shelf
500 mm x 600 mm

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	E25145(120-0500x0600-P112){PSS}	Published catalogue data	31 Oct 2026

01 Model specification

Grade 304 Stainless Steel Preparation Table, 500 mm (L) x 600 mm (W) x 900 mm (H). Worktop Thickness: 2 mm. Undershelf: Perforated Grade 304 1.2 mm. Stainless Steel Frame and Legs with Adjustable Stainless Steel Feet.

Height Specification: 900 mm Working Height (900 mm Overall), Without a Splashback.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	900 mm standard; 850 mm or 1000 mm through advanced customisation.
Overall height	900	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	500	mm	The length of the item typically as measured from left to right.
Width	600	mm	The width of the item typically as measured from front to back.
Material Thickness	2	mm	Grade 304 worktop: fixed at 2 mm for E25145(120).

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Undershelf	Perforated Grade 304 1.2 mm	—	Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Overall height	900	mm

04 Model and supply data

Parent product	E25145(120) – Grade 304 Heavy Duty Preparation Table (2 mm)
Typical lead time	10–15 working days
Warranty	24 months

05 Frequently asked questions

Which worktop thickness belongs to this range?

E25145(120) has a fixed 2 mm Grade 304 worktop. Other worktop thicknesses have separate product ranges.

What is the standard working height?

The standard working height is 900 mm.

Which undershelf options are available?

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

Which sizes are available?

Lengths: 500, 900, 1200, 1500, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Select the required length, width and undershelf specification in the configurator.

Which advanced options are available?

Advanced working heights are 850 mm and 1000 mm. Working height equals overall height because no splashback is fitted.

What supports the worktop?

A stainless steel sub-frame supports the worktop, with no timber or galvanised backing beneath it.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.