

PRODUCT RANGE SPECIFICATION

E25145(120) – Grade 304 Heavy Duty Preparation Table (2 mm)



PRODUCT IMAGE · Rendered
E25145(112-1800x0600), 1800 x 600 x 900 mm, with no undershelf and no splashback.

Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E25145(120){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

31 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

<https://basterfield.co.za/products/e25145120-grade-304-heavy-duty-preparation-table-2-mm#specifications>



01 Product description and specification

Product description

Grade 304 table with a fixed 2 mm worktop, adjustable feet and a choice of no undershelf, solid, slatted, perforated or tubular undershelf.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield E25145(120). The worktop is Grade 304 stainless steel, 2 mm thick. Standard working height is 900 mm. No splashback. The worktop, sub-frame, framework and legs are Grade 304 stainless steel. Stainless steel support is used throughout, with no timber or galvanised backing beneath the worktop. Adjustable stainless steel feet allow levelling on uneven floors. Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration. Confirm the selected item dimensions, undershelf specification and mass on its item specification sheet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Product Range	Heavy Duty	—	—
Splashback Configuration	None	—	—

03 Configuration options

Length	500 mm; 900 mm; 1200 mm; 1500 mm; 1800 mm; 2000 mm; 2400 mm
Width	600 mm; 650 mm; 700 mm
Undershelf specification	No undershelf; Perforated Grade 304 1.2 mm; Perforated Grade 430 1.2 mm; Slatted Grade 304 1.2 mm; Slatted Grade 430 1.2 mm; Solid Grade 304 0.9 mm; Solid Grade 304 1.2 mm; Solid Grade 430 0.9 mm; + 3 more
Worktop thickness	2 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01	Grade 304 stainless steel worktop and frame The worktop is Grade 304 stainless steel, 2 mm thick. Standard working height is 900 mm. Advanced working heights are 850 mm and 1000 mm. Working height equals overall height because no splashback is fitted.
02	No timber or galvanised backing beneath the worktop Stainless steel support beneath the worktop.
03	Adjustable stainless steel feet Adjustable stainless steel feet allow accurate levelling.
04	Choice of undershelf configuration Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.
05	Choice of table sizes Lengths: 500, 900, 1200, 1500, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Select the required length, width and undershelf specification in the configurator.

05 Application information

Intended applications	Food Preparation Workstations, Healthcare Utility Rooms, Laboratory Work Areas, Pharmaceutical Support Areas, Slaughter & Abattoir Operations
Industries	Cannabis, Clinical Laboratories, Hospitals & Clinics, Hotels & Lodges, Institutional & Contract Catering, Meat & Poultry Processing, Pharmaceutical Manufacturing, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

07 Frequently asked questions

Which worktop thickness belongs to this range? E25145(120) has a fixed 2 mm Grade 304 worktop. Other worktop thicknesses have separate product ranges.
What is the standard working height? The standard working height is 900 mm.
Which undershelf options are available? Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

Which sizes are available?

Lengths: 500, 900, 1200, 1500, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Select the required length, width and undershelf specification in the configurator.

Which advanced options are available?

Advanced working heights are 850 mm and 1000 mm. Working height equals overall height because no splashback is fitted.

What supports the worktop?

A stainless steel sub-frame supports the worktop, with no timber or galvanised backing beneath it.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.