MODEL SPECIFICATION

E25145(209-0500x0600-L212) – Eco Table, Slatted Shelf 500 mm x 600 mm

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E25145(209-0500x0600-L212){PSS}	15 Nov 2026

01 Model specification

Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W) x 900 mm (H). Worktop Thickness: 0.9 mm. Undershelf: Slatted Grade 430 1.2 mm. Stainless Steel Frame with Adjustable Feet.

Height Specification: 900 mm Working Height (900 mm Overall), Without a Splashback.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	The standard working height is 900 mm. Advanced customisation offers 850 mm or 1000 mm working heights.
Overall height	900	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Length	500	mm	The length of the item typically as measured from left to right.
Width	600	mm	The width of the item typically as measured from front to back.
Undershelf	Slatted Grade 430 1.2 mm	–	Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.
Material	Stainless Steel Grade 430	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material Thickness	0.9	mm	The worktop is Grade 430 stainless steel, 0.9 mm thick. Choose a separate table range when a thicker worktop is required.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Overall height	900	mm

04 Model and supply data

Parent product	E25145(209) — Grade 430 Eco Preparation Table (0.9 mm)
Typical lead time	10–15 working days
Warranty	24 months

05 Frequently asked questions

What is the standard configuration?

The standard worktop is 0.9 mm thick and the standard working height is 900 mm. The worktop is Grade 430 stainless steel. Stainless steel frame with adjustable feet.

Which undershelf options are available?

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

Which sizes are available?

Lengths: 500, 900, 1200, 1500, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Available combinations vary by undershelf and worktop specification; select the required options in the configurator.

Which advanced options are available?

Advanced customisation offers 850 mm or 1000 mm working heights.

How is the height measured?

This table has no splashback. Working height is measured from the floor to the worktop and equals overall height.

Can I choose another stainless steel grade?

The worktop and table range remain Grade 430; the selected undershelf specification is shown separately. Whole-table Grade 304, Grade 430 and Grade 316 tables remain separate product alternatives. Grade 316 tables are outside the Eco range.

E&OE. Specifications are subject to change without notice.