PRODUCT RANGE SPECIFICATION

# E25145(209) – Grade 430 Eco Preparation Table (0.9 mm)

| DOCUMENT SCOPE | DOCUMENT REFERENCE | DATA STATUS | GENERATED ON |
|---|---|---|---|
| Product range | E25145(209){PSS} | Published catalogue data | 25 Oct 2026 |

**Detailed item specifications**

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e25145209-grade-430-eco-preparation-table-09-mm#specifications

## 01 Product description and specification

**Product description**

Grade 430 table with a 0.9 mm standard worktop, adjustable feet and a choice of no undershelf, solid, slatted, perforated or tubular undershelf.

**Short Form Specification**

**SPECIFICATION USE**
Use this description when specifying this product range.

Basterfield E25145(209). The standard worktop is 0.9 mm thick and the standard working height is 900 mm. The worktop is Grade 430 stainless steel. Stainless steel frame with adjustable feet. This table has no splashback. Working height is measured from the floor to the worktop and equals overall height. Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration. Confirm the selected configuration's dimensions, undershelf material, thickness and mass on its item specification sheet.

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| Material | Stainless Steel Grade 430 | – | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| Material Thickness | 0.9 | mm | The worktop is Grade 430 stainless steel, 0.9 mm thick. Choose a separate table range when a thicker worktop is required. |
| Product Range | Eco | – | – |
| Splashback Configuration | None | – | – |

## 03 Configuration options

| | |
|---|---|
| Length | 500 mm; 900 mm; 1200 mm; 1500 mm; 1800 mm; 2000 mm; 2400 mm |
| Width | 600 mm; 650 mm; 700 mm |


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

| | |
|---|---|
| **Undershelf specification** | No undershelf; Perforated Grade 304 1.2 mm; Perforated Grade 430 1.2 mm; Slatted Grade 304 1.2 mm; Slatted Grade 430 1.2 mm; Solid Grade 304 0.9 mm; Solid Grade 304 1.2 mm; Solid Grade 430 0.9 mm; + 3 more |

Options vary by model; not every combination is available. Use the product page to select a model.

## 04 Functional features

**01 Grade 430 worktop**

The worktop is Grade 430 stainless steel, 0.9 mm thick. Choose a separate table range when a thicker worktop is required.

**02 Economical catering range**

An economical preparation table for catering kitchens and foodservice work areas, with a stainless steel frame and adjustable feet. Eco refers to the economical product range.

**03 Adjustable feet**

Adjustable feet allow levelling at the selected working height.

**04 Choice of undershelf configuration**

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

**05 Size and height choices**

Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The standard working height is 900 mm. Advanced customisation offers 850 mm or 1000 mm working heights.

## 05 Application information

| | |
|---|---|
| **Intended applications** | Food Preparation Workstations |
| **Industries** | Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés |

## 06 Supply and support

| | |
|---|---|
| **Typical lead time** | 10–15 working days |
| **Warranty** | 12 months |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357