

MODEL SPECIFICATION

**E25145(209-0500x0600-T212) – Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W) x 900 mm (H). Worktop thickness: 0.9 mm. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.**

|                |                                 |                          |              |
|----------------|---------------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE              | DATA STATUS              | GENERATED ON |
| Model          | E25145(209-0500x0600-T212){PSS} | Published catalogue data | 15 Sep 2026  |

01 Technical specifications

| PARAMETER          | VALUE                                   | UNIT | TECHNICAL NOTE                                                                                                                                      |
|--------------------|-----------------------------------------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Length             | 500                                     | mm   | The length of the item typically as measured from left to right.                                                                                    |
| Height             | 900                                     | mm   | The standard working height is 900 mm. Advanced customisation offers 850 mm or 1000 mm working heights.                                             |
| Width              | 600                                     | mm   | The width of the item typically as measured from front to back.                                                                                     |
| Undershelf         | Tubular Grade 430 1.2 mm (open section) | –    | Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal. |
| Material           | Stainless Steel Grade 430               | –    | The primary material used in the construction of the item. Certain components may be manufactured from different materials.                         |
| Material Thickness | 0.9                                     | mm   | The worktop is Grade 430 stainless steel, 0.9 mm thick. Choose a separate table range when a thicker worktop is required.                           |

02 Model and supply data

|                   |                                                                                  |
|-------------------|----------------------------------------------------------------------------------|
| Parent product    | E25145(209-T) – Grade 430 Eco Preparation Table (0.9 mm) with Tubular Undershelf |
| Typical lead time | 10–15 working days                                                               |

|          |           |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.