MODEL SPECIFICATION

E25145(212-0500x0600-S212) – Eco Table, Solid Shelf 500 mm x 600 mm

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	E25145(212-0500x0600-S212){PSS}	Published catalogue data	25 Oct 2026

01 Model specification

Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W) x 900 mm (H). Worktop Thickness: 1.2 mm. Undershelf: Solid Grade 430 1.2 mm. Stainless Steel Frame with Adjustable Feet.

Height Specification: 900 mm Working Height (900 mm Overall), Without a Splashback.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	The standard working height is 900 mm. Advanced customisation offers 850 mm or 1000 mm working heights.
Overall height	900	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Undershelf	Solid Grade 430 1.2 mm	–	Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.
Material Thickness	1.2	mm	The worktop is Grade 430 stainless steel, 1.2 mm thick. A 1.5 mm or 2 mm worktop is available through advanced customisation.
Length	500	mm	The length of the item typically as measured from left to right.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Width	600	mm	The width of the item typically as measured from front to back.
Material	Stainless Steel Grade 430	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Overall height	900	mm

04 Model and supply data

Parent product	E25145(212) – Grade 430 Eco Preparation Table (1.2 mm)
Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357