PRODUCT RANGE SPECIFICATION

E25145(212) – Grade 430 Eco Preparation Table (1.2 mm)

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	E25145(212){PSS}	Published catalogue data	25 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e25145212-grade-430-eco-preparation-table-12-mm#specifications

01 Product description and specification

Product description

Grade 430 table with a 1.2 mm standard worktop, adjustable feet and a choice of no undershelf, solid, slatted, perforated or tubular undershelf.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield E25145(212). The standard worktop is 1.2 mm thick and the standard working height is 900 mm. The worktop is Grade 430 stainless steel. Stainless steel frame with adjustable feet. This table has no splashback. Working height is measured from the floor to the worktop and equals overall height. Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration. Confirm the selected configuration's dimensions, undershelf material, thickness and mass on its item specification sheet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 430	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Product Range	Eco	–	–
Splashback Configuration	None	–	–

03 Configuration options

Length	500 mm; 900 mm; 1200 mm; 1500 mm; 1800 mm; 2000 mm; 2400 mm
Width	600 mm; 650 mm; 700 mm
Undershelf specification	No undershelf; Perforated Grade 304 1.2 mm; Perforated Grade 430 1.2 mm; Slatted Grade 304 1.2 mm; Slatted Grade 430 1.2 mm; Solid Grade 304 0.9 mm; Solid Grade 304 1.2 mm; Solid Grade 430 0.9 mm; + 3 more

Options vary by model; not every combination is available. Use the product page to select a model.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

04 Functional features

01 Grade 430 worktop

The worktop is Grade 430 stainless steel, 1.2 mm thick. A 1.5 mm or 2 mm worktop is available through advanced customisation.

02 Economical catering range

An economical preparation table for catering kitchens and foodservice work areas, with a stainless steel frame and adjustable feet. Eco refers to the economical product range.

03 Adjustable feet

Adjustable feet allow levelling at the selected working height.

04 Choice of undershelf configuration

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

05 Size and height choices

Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The standard working height is 900 mm. Advanced customisation offers 850 mm or 1000 mm working heights.

05 Application information

Intended applications	Food Preparation Workstations
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357