

PRODUCT RANGE SPECIFICATION

E27292 – Heavy Duty Pot Drying Rack



PRODUCT IMAGE - 1200mm x 750mm variant shown. Choose the required length and width.

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E27292{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

12 Oct 2026

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

<https://basterfield.co.za/products/e27292-heavy-duty-pot-drying-rack#specifications>



01 Product description and specification

Product description

Heavy duty Grade 304 stainless steel pot drying rack with a 40 × 40mm square tubular frame, cross bracing, Ø28mm round tube cross members and stainless steel adjustable feet. Four lengths and three widths, all 900mm high.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Heavy duty Grade 304 stainless steel pot drying rack. Lengths: 1000mm, 1200mm, 1500mm or 2000mm. Widths: 650mm standard, 700mm or 750mm. Overall height: 900mm. 40 × 40mm square tubular frame with cross bracing, Ø28mm round tube cross members and stainless steel adjustable feet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Height	900	mm	Overall rack height: 900mm across all size variants.
Material	Stainless Steel Grade 304	—	Grade 304 stainless steel framework and round tube cross members.
Mounting Type	Free Standing	—	Freestanding rack supported by its tubular frame and adjustable feet.
Adjustable Feet	Yes	—	Stainless steel adjustable feet for levelling the rack during installation.
Cross Bracing	Yes	—	Cross bracing supports the rack frame and helps maintain rigidity.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Framework Material	Stainless Steel Grade 304	—	Grade 304 stainless steel framework and round tube cross members.
Framework Profile	40 × 40mm Square Tubular Framework	—	40mm × 40mm square tubular stainless steel framework.
Feet Material	Stainless Steel	—	The adjustable feet are stainless steel.
Construction	Heavy Duty Cross-Braced Tubular Construction	—	Heavy duty tubular construction with a cross-braced frame and open tubular drying surface.
Cross Member Diameter	28	mm	Ø28mm round tube cross members form the drying surface.

03 Models and configurations

ITEM CODE	LENGTH	WIDTH
E27292(1000)	1000 mm	650 mm
E27292(1000x0700)	1000 mm	700 mm
E27292(1000x0750)	1000 mm	750 mm
E27292(1200)	1200 mm	650 mm
E27292(1200x0700)	1200 mm	700 mm
E27292(1200x0750)	1200 mm	750 mm
E27292(1500)	1500 mm	650 mm
E27292(1500x0700)	1500 mm	700 mm
E27292(1500x0750)	1500 mm	750 mm
E27292(2000)	2000 mm	650 mm
E27292(2000x0700)	2000 mm	700 mm
E27292(2000x0750)	2000 mm	750 mm

04 Functional features

01	Open Tubular Drying Surface The spaced round-tube cross members support washed pots and utensils while allowing water to drip through the rack.
02	40 × 40mm Square Tubular Frame A substantial Grade 304 stainless steel frame provides a robust structure for heavy duty use in busy wash-up areas.
03	Cross-Braced Framework Cross bracing supports the frame and helps maintain rigidity during routine loading and unloading.
04	Ø28mm Round Tube Cross Members Grade 304 stainless steel round tubular supports form the open drying surface for washed pots and suitable utensils.
05	Stainless Steel Adjustable Feet Adjustable feet allow the rack to be levelled during installation.
06	900mm Height All sizes share a 900mm overall height for placing and removing washed items.

07 Twelve Size Options

Choose 1000mm, 1200mm, 1500mm or 2000mm length, each available in 650mm, 700mm or 750mm width. The standard width is 650mm.

05 Application information

Intended applications	Kitchen Washing & Warewashing, Pot Washing
Industries	Food & Beverage Processing, Hospitality & Foodservice, Institutional & Contract Catering

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.