MODEL SPECIFICATION

# E27292(2T-1000x0700) – Pot Drying Rack Two Tier 1000mm (L) x 700mm (W)

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | E27292(2T-1000x0700){PSS} | 25 Nov 2026 |

## 01 Model specification

Pot Drying Rack, Stainless Steel Grade 304, 1000mm (L) x 700mm (W) x 900mm (H), with Two Drying Tiers, 40mm × 40mm Square Tubular Framework, Ø28mm Cross Members and Stainless Steel Adjustable Feet. The lower rack is 250mm above the floor.

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Working Height** | 900 | mm | Height above the floor to the top drying rack. |
| **Overall height** | 900 | mm | Overall rack height, measured from the floor to the top drying rack. |
| **Material** | Stainless Steel Grade 304 | – | Grade 304 stainless steel framework and round tube cross members. |
| **Width** | 700 | mm | The width of the item typically as measured from front to back. |
| **Length** | 1000 | mm | The length of the item typically as measured from left to right. |
| **Shelf Tiers** | 2 | – | Number of drying racks fitted to the frame. |
| **Framework Material** | Stainless Steel Grade 304 | – | – |
| **Framework Profile** | 40 × 40mm Square Tubular Framework | – | 40 × 40mm square tubular Grade 304 stainless steel framework. |
| **Mounting Type** | Free Standing | – | – |
| **Adjustable Feet** | Yes | – | – |
| **Feet Material** | Stainless Steel | – | – |
| **Construction** | Heavy Duty Two Tier Tubular Construction | – | Two drying racks, with the top rack 900mm and the lower rack 250mm above the floor. |
| **Cross Bracing** | No | – | The lower drying rack replaces the cross bracing at 250mm above the floor. |


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| Cross Member Diameter | 28 | mm | Outside diameter of round tubular cross members. |
| Lower Rack Height | 250 | mm | Height above the finished floor. |

## 03 Dimensions and mass

| PARAMETER | VALUE | UNIT |
|---|---|---|
| Length | 1000 | mm |
| Width | 700 | mm |
| Overall height | 900 | mm |

## 04 Model and supply data

| | |
|---|---|
| Parent product | E27292(2T) — Heavy Duty Two Tier Pot Drying Rack |
| Typical lead time | 10–15 working days |
| Warranty | 24 months |

## 05 Specification notes

**Configuration description**

Heavy duty two tier Grade 304 stainless steel pot drying rack, 1000mm long and 700mm wide. The top drying rack is 900mm above the floor, with a second drying rack at 250mm above the floor in place of lower cross bracing. The 40 × 40mm square tubular framework supports open drying surfaces formed by Ø28mm round tube cross members. Stainless steel adjustable feet allow levelling during installation. Suitable for supporting washed pots and utensils for drip drying.

**Short Form Specification**

> **SPECIFICATION USE**
> Use this description when specifying this model.

Grade 304 stainless steel two tier pot drying rack, 1000mm (L) × 700mm (W) × 900mm (H). The top drying rack is 900mm above the floor, with a second drying rack at 250mm above the floor in place of lower cross bracing. 40 × 40mm square tubular frame, Ø28mm round tube cross members and stainless steel adjustable feet.

**Detailed specification**

- Model: E27292(2T-1000x0700)
- Drying Tiers: 2
- Overall Dimensions: 1000mm (L) × 700mm (W) × 900mm (H)
- Top Rack Height Above Floor: 900mm
- Lower Rack Height Above Floor: 250mm
- Lower Support: Additional Drying Rack in Place of Cross Bracing
- Material: Stainless Steel Grade 304
- Framework: 40 × 40mm Square Tubular Grade 304 Stainless Steel
- Cross Members: Ø28mm Round Tube
- Feet: Stainless Steel Adjustable Feet
- Mounting: Freestanding
- Intended Use: Supporting Washed Pots and Suitable Utensils for Drip Drying

## 06 Frequently asked questions

**What is the pot drying rack used for?**

It provides a place for washed pots, utensils and other suitable items to drip dry after washing in commercial kitchens, sculleries and food preparation areas.

**Which sizes are available?**

There are twelve standard combinations: 1000mm, 1200mm, 1500mm and 2000mm lengths, each available in 650mm, 700mm or 750mm width. The top drying rack is 900mm above the floor on every model.

**Which width is standard?**

650mm is the standard width. Wider 700mm and 750mm variants are available at every listed length.

**How is the frame constructed?**

The rack has 40 × 40mm square tubular Grade 304 stainless steel framework, Ø28mm round tube cross members and stainless steel adjustable feet. The top drying rack is 900mm above the floor. A second drying rack at 250mm above the floor replaces the lower cross bracing.

**What stainless steel grade is used?**

The framework and round tube cross members are manufactured from Grade 304 stainless steel. The adjustable feet are stainless steel.

**Can the rack be levelled?**

Yes. Stainless steel adjustable feet allow levelling during installation.

**How should I choose a rack size?**

Check the available floor space and the footprint of the items to be dried. Choose a length and width that support the items securely across the tubular drying surface.

**What are the rack and support heights?**

The top drying rack is 900mm above the floor. A second drying rack at 250mm above the floor replaces the lower cross bracing.

E&OE. Specifications are subject to change without notice.


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357