PRODUCT RANGE SPECIFICATION

E27292(2T) – Heavy Duty Two Tier Pot Drying Rack



PRODUCT IMAGE · Representative two tier pot drying rack; dimensions vary by model.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**E27292(2T){PSS}**	**25 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e272922t-heavy-duty-two-tier-pot-drying-rack#specifications

01 Product description and specification

Product description

Heavy duty Grade 304 stainless steel two tier pot drying rack. Top rack at 900mm, with a lower drying rack at 250mm above the floor. Four lengths and three widths.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Heavy duty two tier Grade 304 stainless steel pot drying rack. Lengths: 1000mm, 1200mm, 1500mm or 2000mm. Widths: 650mm standard, 700mm or 750mm. The top drying rack is 900mm above the floor. A second drying rack at 250mm above the floor replaces the lower cross bracing. 40 × 40mm square tubular frame, Ø28mm round tube cross members and stainless steel adjustable feet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Height above the floor to the top drying rack.
Overall height	900	mm	Overall rack height, measured from the floor to the top drying rack.
Material	Stainless Steel Grade 304	–	Grade 304 stainless steel framework and round tube cross members.
Mounting Type	Free Standing	–	–
Adjustable Feet	Yes	–	–
Framework Material	Stainless Steel Grade 304	–	–

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Framework Profile	40 × 40mm Square Tubular Framework	–	40 × 40mm square tubular Grade 304 stainless steel framework.
Feet Material	Stainless Steel	–	–
Construction	Heavy Duty Two Tier Tubular Construction	–	Two drying racks, with the top rack 900mm and the lower rack 250mm above the floor.
Cross Member Diameter	28	mm	Outside diameter of round tubular cross members.
Shelf Tiers	2	–	Number of drying racks fitted to the frame.
Cross Bracing	No	–	The lower drying rack replaces the cross bracing at 250mm above the floor.
Lower Rack Height	250	mm	Height above the finished floor.

03 Configuration options

Length	1000 mm; 1200 mm; 1500 mm; 2000 mm
Width	650 mm; 700 mm; 750 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 **Open Tubular Drying Surface**
The spaced round-tube cross members support washed pots and utensils while allowing water to drip through the rack.

02 **40 × 40mm Square Tubular Frame**
A substantial Grade 304 stainless steel frame provides a robust structure for heavy duty use in busy wash-up areas.

03 **Lower Drying Rack at 250mm**
A second drying rack 250mm above the floor replaces the lower cross bracing.

04 **Ø28mm Round Tube Cross Members**
Grade 304 stainless steel round tubular supports form the open drying surface for washed pots and suitable utensils.

05 **Stainless Steel Adjustable Feet**
Adjustable feet allow the rack to be levelled during installation.

06 **Top Rack at 900mm**
The top drying rack is 900mm above the floor on every size.

07 **Twelve Size Options**
Choose 1000mm, 1200mm, 1500mm or 2000mm length, each available in 650mm, 700mm or 750mm width. The standard width is 650mm.

05 Application information

Intended applications	Kitchen Washing & Warewashing, Pot Washing
Industries	Food & Beverage Processing, Hospitality & Foodservice, Institutional & Contract Catering

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

07 Frequently asked questions

What is the pot drying rack used for?

It provides a place for washed pots, utensils and other suitable items to drip dry after washing in commercial kitchens, sculleries and food preparation areas.

Which sizes are available?

There are twelve standard combinations: 1000mm, 1200mm, 1500mm and 2000mm lengths, each available in 650mm, 700mm or 750mm width. The top drying rack is 900mm above the floor on every model.

Which width is standard?

650mm is the standard width. Wider 700mm and 750mm variants are available at every listed length.

How is the frame constructed?

The rack has 40 × 40mm square tubular Grade 304 stainless steel framework, Ø28mm round tube cross members and stainless steel adjustable feet. The top drying rack is 900mm above the floor. A second drying rack at 250mm above the floor replaces the lower cross bracing.

What stainless steel grade is used?

The framework and round tube cross members are manufactured from Grade 304 stainless steel. The adjustable feet are stainless steel.

Can the rack be levelled?

Yes. Stainless steel adjustable feet allow levelling during installation.

How should I choose a rack size?

Check the available floor space and the footprint of the items to be dried. Choose a length and width that support the items securely across the tubular drying surface.

What are the rack and support heights?

The top drying rack is 900mm above the floor. A second drying rack at 250mm above the floor replaces the lower cross bracing.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357