PRODUCT RANGE SPECIFICATION

E27293(4T) – Heavy Duty Four Tier Pot Drying Rack with Centre Supports



PRODUCT IMAGE · Representative four tier pot drying rack with centre upright supports; dimensions vary by model.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	E27293(4T){PSS}	Published catalogue data	5 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e272934t-heavy-duty-four-tier-pot-drying-rack-with-centre-supports#specifications

01 Product description and specification

Product description

Heavy duty four tier Grade 304 stainless steel pot drying rack with centre upright supports. Available in 2500mm and 3000mm lengths, with 450mm tier pitch.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Four tier Grade 304 stainless steel pot drying rack, available in 2500mm or 3000mm length, 750mm wide and 1600mm high. 450mm vertical tier pitch, heavy duty 40 × 40mm square tubular framework, additional centre upright supports, Ø28mm round tube cross members and stainless steel adjustable feet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Height	1600	mm	Overall rack height above the floor.
Material	Stainless Steel Grade 304	–	Grade 304 stainless steel framework and round tube cross members.
Shelf Tiers	4	–	Number of drying tiers fitted to the frame.
Tier Pitch	450	mm	Vertical repeat distance between corresponding points on adjacent tiers; not the clear gap between tiers.
Framework Material	Stainless Steel Grade 304	–	–
Framework Profile	40 × 40mm Square Tubular Framework	–	Heavy duty 40 × 40mm square tubular framework.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Centre Upright Supports	Yes	–	Additional upright supports at the centre of the rack length, for the E27293 range designed for lengths greater than 2000mm.
Cross Member Diameter	28	mm	Outside diameter of the round tube cross members.
Adjustable Feet	Yes	–	Stainless steel adjustable feet allow levelling during installation.
Feet Material	Stainless Steel	–	–
Mounting Type	Free Standing	–	–
Construction	Heavy Duty Four Tier Tubular Construction with Centre Upright Supports	–	Four drying tiers at 450mm vertical pitch, with additional centre upright supports.

03 Configuration options

Length	2500 mm; 3000 mm
Width	750 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 **Grade 304 Stainless Steel**
Grade 304 stainless steel framework and round tube cross members.

02 **Four Tiers at 450mm Pitch**
Four open drying tiers with a vertical pitch of 450mm.

03 **Centre Upright Supports**
Additional upright supports at the centre of the length for the E27293 range designed for lengths greater than 2000mm.

04 **40 × 40mm Tubular Framework**
Heavy duty square tubular framework supports the four drying tiers.

05 **Ø28mm Round Tube Cross Members**
Open tubular drying surfaces support washed pots and suitable utensils.

06 **Stainless Steel Adjustable Feet**
Adjustable feet allow levelling during installation.

07 **2500mm and 3000mm Lengths**
Both lengths are 750mm wide and 1600mm high.

05 Application information

Intended applications	Kitchen Washing & Warewashing, Pot Washing
Industries	Food & Beverage Processing, Hospitality & Foodservice, Institutional & Contract Catering

06 Supply and support

Typical lead time	10–15 working days

06 Supply and support

Warranty	24 months

07 Frequently asked questions

What is this pot drying rack used for?

It supports washed pots and suitable utensils for drip drying in commercial kitchens, sculleries and food preparation areas.

Which sizes are available?

The four tier rack is available in 2500mm and 3000mm lengths. Both versions are 750mm wide and 1600mm high.

How does E27293 differ from the E27292 range?

E27293 is designed for lengths greater than 2000mm and includes additional upright supports at the centre of its length. These four tier models retain the Grade 304 stainless steel, 40 × 40mm square tubular framework, Ø28mm round tube cross members and stainless steel adjustable feet used in the E27292 range.

How are the tiers spaced?

There are four drying tiers with a vertical pitch of 450mm. Pitch is the repeat distance between corresponding points on adjacent tiers; it is not the clear gap between tiers.

How is the rack constructed?

The rack has heavy duty 40 × 40mm square tubular Grade 304 stainless steel framework, additional centre upright supports and open drying surfaces formed by Ø28mm round tube cross members.

Can the rack be levelled?

Yes. Stainless steel adjustable feet allow levelling during installation.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357