

PRODUCT RANGE SPECIFICATION

E27293(4T) – Heavy Duty Four Tier Pot Drying Rack with Centre Supports



PRODUCT IMAGE · Representative four tier pot drying rack with centre upright supports; dimensions vary by model.

Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE
Product range

DOCUMENT REFERENCE
E27293(4T){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
14 Oct 2026

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

<https://basterfield.co.za/products/e272934t-heavy-duty-four-tier-pot-drying-rack-with-centre-supports#specifications>



01 Product description and specification

Product description
Heavy duty four tier Grade 304 stainless steel pot drying rack with centre upright supports. Available in 2500mm and 3000mm lengths, with 450mm tier pitch.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Four tier Grade 304 stainless steel pot drying rack, available in 2500mm or 3000mm length, 750mm wide and 1600mm high. 450mm vertical tier pitch, heavy duty 40 × 40mm square tubular framework, additional centre upright supports, Ø28mm round tube cross members and stainless steel adjustable feet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Height	1600	mm	Overall rack height above the floor.
Material	Stainless Steel Grade 304	—	Grade 304 stainless steel framework and round tube cross members.
Shelf Tiers	4	—	Number of drying tiers fitted to the frame.
Tier Pitch	450	mm	Vertical repeat distance between corresponding points on adjacent tiers; not the clear gap between tiers.
Framework Material	Stainless Steel Grade 304	—	—
Framework Profile	40 × 40mm Square Tubular Framework	—	Heavy duty 40 × 40mm square tubular framework.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Centre Upright Supports	Yes	—	Additional upright supports at the centre of the rack length, for the E27293 range designed for lengths greater than 2000mm.
Cross Member Diameter	28	mm	Outside diameter of the round tube cross members.
Adjustable Feet	Yes	—	Stainless steel adjustable feet allow levelling during installation.
Feet Material	Stainless Steel	—	—
Mounting Type	Free Standing	—	—
Construction	Heavy Duty Four Tier Tubular Construction with Centre Upright Supports	—	Four drying tiers at 450mm vertical pitch, with additional centre upright supports.

03 Models and configurations

Common to all models: Width: 750 mm	
ITEM CODE	LENGTH
E27293(4T-2500x0750)	2500 mm
E27293(4T-3000x0750)	3000 mm

04 Functional features

01	Grade 304 Stainless Steel Grade 304 stainless steel framework and round tube cross members.
02	Four Tiers at 450mm Pitch Four open drying tiers with a vertical pitch of 450mm.
03	Centre Upright Supports Additional upright supports at the centre of the length for the E27293 range designed for lengths greater than 2000mm.
04	40 × 40mm Tubular Framework Heavy duty square tubular framework supports the four drying tiers.
05	Ø28mm Round Tube Cross Members Open tubular drying surfaces support washed pots and suitable utensils.
06	Stainless Steel Adjustable Feet Adjustable feet allow levelling during installation.
07	2500mm and 3000mm Lengths Both lengths are 750mm wide and 1600mm high.

05 Application information

Intended applications	Kitchen Washing & Warewashing, Pot Washing
Industries	Food & Beverage Processing, Hospitality & Foodservice, Institutional & Contract Catering

Typical lead time	10–15 working days
Warranty	24 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.