

MODEL SPECIFICATION

E48925(050) – Pressure Steam
Cooker Electric S/Steel 304 Heavy
Duty 50L



PRODUCT IMAGE

DOCUMENT SCOPE

Model

DOCUMENT REFERENCE

E48925(050){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Capacity	50	L	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Finish	Satin	—	—

02 Model and supply data

Parent product	E48925 – Electric Pressure Steam Cooker
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description

Basterfield E48925(050), 50-litre pressure cooker. Manufactured in South Africa from heavy-duty Grade 304 stainless steel with a satin finish.

Batch meal preparation for catering, restaurants and institutional kitchens. Detachable electric stove; electrical connection as specified for the selected model.

Pressure gauge, clamping lid, heat-resistant handles, safety control valve and overpressure plug. 80 kPa standard regulator; optional 35 kPa or 68 kPa regulator weights.

Follow the supplied operating instructions and loading limits. Cooking beans and lentils is not recommended. Trivets and cooking inserts are optional extras.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this model.

Basterfield E48925(050), 50-litre pressure cooker. Manufactured in South Africa from heavy-duty Grade 304 stainless steel with a satin finish. Detachable electric stove; electrical connection as specified for the selected model. 80 kPa standard regulator; optional 35 kPa or 68 kPa regulator weights. Pressure gauge, clamping lid, heat-resistant handles, safety control valve and overpressure plug. Cooking accessories specified separately.

Detailed specification	• Model: E48925(050) • Capacity: 50 L • Material: Grade 304 stainless steel • Finish: Satin • Manufacture: South Africa • Construction: Heavy-duty vessel and bottom • Lid: Swing clamps and wing nuts • Handles: Heat-resistant, on vessel and lid • Pressure monitoring: Gauge • Pressure relief: Safety control valve and overpressure plug • Heating: Detachable electric stove; electrical connection as specified for the selected model. • Regulator: 80 kPa standard regulator; optional 35 kPa or 68 kPa regulator weights.
------------------------	--

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.