

MODEL SPECIFICATION

E48965(040) – Grade 304 Stainless Steel Electric Pressure Canner, 40 L with a 2 kW Heating Base. Indicative Jar Capacity: 27 x 500 ml Jars (Three Layers Stacked) or 18 x 1000 ml Jars (Stacked). Jar Capacities Are Indicative and Depend on the Actual Dimensions of the Jars Used.



PRODUCT IMAGE

DOCUMENT SCOPE
Model

DOCUMENT REFERENCE
E48965(040){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Capacity	40	L	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Finish	Satin	—	—

02 Model and supply data

Parent product	E48965 – Electric Stainless Steel Pressure Canner
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	Basterfield E48965(040), 40-litre pressure canner. Manufactured in South Africa from heavy-duty Grade 304 stainless steel with a satin finish. Food preservation in jars for households, homesteads, farms, orchards and food-production settings. Detachable 2 kW electric base with energy regulator; not direct induction or coal-fire use. Pressure gauge, clamping lid, heat-resistant handles, safety control valve and overpressure plug. 103.4 kPa standard regulator; optional 80 kPa regulator. Indicative jar capacity: 27 x 500 ml jars (three layers stacked) or 18 x 1000 ml jars (stacked). Jar capacities are indicative and depend on the actual dimensions of the jars used. Confirm overall dimensions including the heating base for the selected model. Specify compatible canning racks separately for the loading arrangement. Follow the supplied operating instructions.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield E48965(040). Grade 304 stainless steel electric pressure canner, 40 L with a 2 kW heating base. Indicative jar capacity: 27 x 500 ml jars (three layers stacked) or 18 x 1000 ml jars (stacked). Jar capacities are indicative and depend on the actual dimensions of the jars used. Satin finish, heavy-duty vessel and bottom, clamping lid, heat-resistant handles, pressure gauge, safety control valve and overpressure plug. Manufactured in South Africa.
Detailed specification	• Model: E48965(040) • Vessel capacity: 40 L • Indicative jar capacity: 27 x 500 ml jars (three layers stacked) or 18 x 1000 ml jars (stacked). • Jar-fit note: Jar capacities are indicative and depend on the actual dimensions of the jars used. • Material: Grade 304 stainless steel • Finish: Satin • Manufacture: South Africa • Construction: Heavy-duty vessel and bottom • Lid: Swing clamps and wing nuts • Handles: Heat-resistant, on vessel and lid • Pressure monitoring: Gauge • Pressure relief: Safety control valve and overpressure plug • Heating: Detachable 2 kW electric base with energy regulator; not direct induction or coal-fire use. • Regulator: 103.4 kPa standard regulator; optional 80 kPa regulator.
VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.	