
PRODUCT RANGE SPECIFICATION

# E55810(0350S) – Countertop Drip Trays with Side Spout



**PRODUCT IMAGE** · 350 x 300 mm model shown. Other sizes vary.

ⓘ Product image is representative of the range and may not reflect the actual item.

| DOCUMENT SCOPE | DOCUMENT REFERENCE | DATA STATUS | GENERATED ON |
|---|---|---|---|
| **Product range** | **E55810(0350S){PSS}** | **Published catalogue data** | **31 Oct 2026** |

**Detailed item specifications**

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e558100350s-countertop-drip-trays-with-side-spout#specifications

## 01 Product description and specification

**Product description**

Grade 304 stainless steel countertop drip trays with removable perforated inserts and side drainage spouts. Choose 350, 450 or 650 mm length and 200 or 300 mm width; all six models are 35 mm high.

**Short Form Specification**

**SPECIFICATION USE**
Use this description when specifying this product range.

Basterfield countertop drip tray with side drainage spout; Grade 304 stainless steel; removable perforated insert. Length: 350, 450 or 650 mm. Width: 200 or 300 mm. Overall height: 35 mm. Allow clearance for the side spout and the selected drainage arrangement.

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Material** | Stainless Steel Grade 304 | – | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| **Drainage** | Side spout | – | – |

## 03 Configuration options

| | |
|---|---|
| **Length** | 350 mm; 450 mm; 650 mm |
| **Width** | 200 mm; 300 mm |

Options vary by model; not every combination is available. Use the product page to select a model.

## 04 Functional features

01 **Side Drainage Spout**
Collected liquid drains through a spout at the side of the tray.

02 **Removable Perforated Insert**
The perforated insert lifts out of the collecting tray.

03 **Grade 304 Stainless Steel**
Stainless steel collecting tray and perforated insert.

04 **Six Countertop Sizes**
Lengths of 350, 450 and 650 mm, each in 200 and 300 mm widths; 35 mm overall height.

## 05 Application information

| | |
|---|---|
| **Intended applications** | Hot Water and Beverage Service |
| **Industries** | Hotels & Lodges, Restaurants & Cafés |

## 06 Supply and support

| | |
|---|---|
| **Typical lead time** | 10–15 working days |
| **Warranty** | 12 months |

## 07 Frequently asked questions

**Which sizes are available?**

Choose 350, 450 or 650 mm length and 200 or 300 mm width. All six models are 35 mm high. The original E55810(0350S) model is 350 x 300 x 35 mm.

**How does the tray drain?**

Position the tray on the countertop with the side spout directed towards a suitable drainage collection point. Allow clearance around the spout and confirm the drainage arrangement for the installation.

**Can the insert be removed?**

Yes. The perforated insert lifts out of the collecting tray.

**Is this the 40 mm BSP waste-outlet range?**

This range drains through a side spout. For a centre outlet suitable for a 40 mm (1½″ BSP) waste fitting and pipework below the counter, select the separate E55810(W) range.

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357