
PRODUCT RANGE SPECIFICATION

E55810(0350S) – Countertop Drip Trays with Side Spout



PRODUCT IMAGE · 350 x 300 mm model shown. Other sizes vary.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**E55810(0350S){PSS}**	**21 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e558100350s-countertop-drip-trays-with-side-spout#specifications

01 Product description and specification

Product description

Grade 304 stainless steel countertop drip trays with removable perforated inserts and side drainage spouts. Choose 350, 450 or 650 mm length and 200 or 300 mm width; all six models are 35 mm high.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield countertop drip tray with side drainage spout; Grade 304 stainless steel; removable perforated insert. Length: 350, 450 or 650 mm. Width: 200 or 300 mm. Overall height: 35 mm. Allow clearance for the side spout and the selected drainage arrangement.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Drainage	Side spout	–	–

03 Configuration options

Length	350 mm; 450 mm; 650 mm
Width	200 mm; 300 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 **Side Drainage Spout**
Collected liquid drains through a spout at the side of the tray.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 **Removable Perforated Insert**
The perforated insert lifts out of the collecting tray.

03 **Grade 304 Stainless Steel**
Stainless steel collecting tray and perforated insert.

04 **Six Countertop Sizes**
Lengths of 350, 450 and 650 mm, each in 200 and 300 mm widths; 35 mm overall height.

05 Application information

Intended applications	Hot Water and Beverage Service
Industries	Hotels & Lodges, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

07 Frequently asked questions

Which sizes are available?

Choose 350, 450 or 650 mm length and 200 or 300 mm width. All six models are 35 mm high. The original E55810(0350S) model is 350 x 300 x 35 mm.

How does the tray drain?

Position the tray on the countertop with the side spout directed towards a suitable drainage collection point. Allow clearance around the spout and confirm the drainage arrangement for the installation.

Can the insert be removed?

Yes. The perforated insert lifts out of the collecting tray.

Is this the 40 mm BSP waste-outlet range?

This range drains through a side spout. For a centre outlet suitable for a 40 mm (1½″ BSP) waste fitting and pipework below the counter, select the separate E55810(W) range.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357