MODEL SPECIFICATION

H50452(112-1300x0700R) – Tub Dog Grooming 1300mm (L) x 700mm (W) Right-Hand



PRODUCT IMAGE · Right-hand version shown.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	H50452(112-1300x0700R){PSS}	19 Nov 2026

01 Model specification

Dog Grooming Tub, Stainless Steel Grade 304, 1.2mm Thickness, 1300mm (L) x 700mm (W), with Right-Hand Foldable Slide-Out Anti-Slip Access Door, Same-Side Ø90mm Waste Outlet and Supplied Basket-Strainer Waste, Minimum 1:100 Fall to Drain, Three Perforated False-Bottom Inserts at Two Adjustable Levels, 40 x 40mm Grade 304 Stainless Steel Tubular Frame and Stainless Steel Adjustable Feet. Lower Insert Height: 850mm; Trough Bottom at Highest Point: 800mm; Trough Depth at Shallow End: 500mm; Front Rim Height: 1300mm; Left, Right and Rear Splashbacks: 300mm with Safety-Hemmed Top Edge; Overall Height: 1600mm. Hose and Trigger Spray Excluded; Available as Optional Accessories.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Width	700	mm	The width of the item typically as measured from front to back.
Splashback Height	300	mm	Vertical height above the front trough rim; the rim is 1300mm above the floor.
Length	1300	mm	The length of the item typically as measured from left to right.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Depth	500	mm	Vertical depth from the highest, shallow end of the trough bottom to the front rim. The bottom slopes down towards the waste.
Trough Depth Measurement	From the Highest, Shallow End to the Front Rim	–	–
False Bottom Insert Type	Perforated	–	–
Height	1600	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Waste Outlet Diameter	90	mm	–
Lower Insert Height	850	mm	Height above the floor of the lower perforated false-bottom insert level.
Trough Bottom Height at Highest Point	800	mm	–
Front Rim Height	1300	mm	–
Framework Material	Stainless Steel Grade 304	–	–
Framework Tube Size	40 x 40 mm	–	–
Feet	Stainless Steel Adjustable Feet	–	–
Splashback Configuration	Rear and Both Sides	–	–
Splashback Top Edge	Safety Hem	–	–
Access Door Type	Foldable Slide-Out Door	–	–
Access Door Surface	Anti-Slip	–	–
Waste Assembly	Basket-Strainer Waste Supplied	–	–
Waste Outlet Position	Same Side as Access Door	–	–
Minimum Drainage Fall	1:100	–	–
False Bottom Insert Quantity	3	–	–
Insert Adjustment Levels	2	–	–
Optional Accessories	Hose and Trigger Spray; Excluded from Tub Price	–	–
Door Orientation	Right-Hand	–	–

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1300	mm
Width	700	mm

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Overall height	1600	mm

04 Model and supply data

Parent product	H50452 — Stainless Steel Dog Grooming Tub
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Configuration description

The H50452 dog grooming tub is made from 1.2mm Grade 304 stainless steel and measures 1300mm long x 700mm wide. This item has a right-hand opening door and the waste is on the same side. The foldable slide-out access door has an anti-slip surface.

Three perforated false-bottom inserts are supplied, with two adjustable levels for different-height dogs. The lower insert is 850mm above the floor. The trough bottom is 800mm above the floor at its highest point and falls towards the waste at a minimum gradient of 1:100. Measured from its shallow end, the trough is 500mm deep to the front working rim. The rim is therefore 1300mm above the floor.

A 90mm pre-punched waste outlet with a supplied basket-strainer waste is positioned on the same side as the door for access and maintenance. 300mm splashbacks above the rim run along the left, right and rear and have a safety hem on the top edge. Overall height is 1600mm.

The frame uses 40 x 40mm Grade 304 stainless steel tubing and stainless steel adjustable feet. The hose and trigger spray are excluded and are available as optional accessories.

Short Form Specification

> **SPECIFICATION USE**
> Use this description when specifying this model.

Dog Grooming Tub, Stainless Steel Grade 304, 1.2mm Thickness, 1300mm (L) x 700mm (W), with Right-Hand Foldable Slide-Out Anti-Slip Access Door, Same-Side Ø90mm Waste Outlet and Supplied Basket-Strainer Waste, Minimum 1:100 Fall to Drain, Three Perforated False-Bottom Inserts at Two Adjustable Levels, 40 x 40mm Grade 304 Stainless Steel Tubular Frame and Stainless Steel Adjustable Feet. Lower Insert Height: 850mm; Trough Bottom at Highest Point: 800mm; Trough Depth at Shallow End: 500mm; Front Rim Height: 1300mm; Left, Right and Rear Splashbacks: 300mm with Safety-Hemmed Top Edge; Overall Height: 1600mm. Hose and Trigger Spray Excluded; Available as Optional Accessories.

Detailed specification

- Item Code: H50452(112-1300x0700R)
- Door Orientation: Right-Hand
- Material: Stainless Steel Grade 304
- Material Thickness: 1.2mm
- Length: 1300mm
- Width: 700mm
- Height: 1600mm
- Bowl Depth: 500mm
- Splashback Height: 300mm
- Trough Depth Measurement: From the Highest, Shallow End to the Front Rim
- Lower Insert Height: 850mm
- Trough Bottom Height at Highest Point: 800mm
- Front Rim Height: 1300mm
- Framework Material: Stainless Steel Grade 304
- Framework Tube Size: 40 x 40 mm
- Feet: Stainless Steel Adjustable Feet
- Splashback Configuration: Rear and Both Sides
- Splashback Top Edge: Safety Hem
- Access Door Type: Foldable Slide-Out Door
- Access Door Surface: Anti-Slip
- Waste Outlet Diameter: 90mm
- Waste Assembly: Basket-Strainer Waste Supplied
- Waste Outlet Position: Same Side as Access Door
- Minimum Drainage Fall: 1:100
- False Bottom Insert Quantity: 3
- False Bottom Insert Type: Perforated
- Insert Adjustment Levels: 2
- Optional Accessories: Hose and Trigger Spray; Excluded from Tub Price
- Overall Height: 1600mm
- Trough Depth Datum: 500mm from the Highest, Shallow End to the Front Rim

06 Frequently asked questions

What are the dimensions?

The tub is 1300mm long and 700mm wide. The front rim is 1300mm above the floor and the overall height, including splashbacks, is 1600mm.

How are the trough and insert heights specified?

The lower false-bottom insert is 850mm above the floor. The trough bottom is 800mm above the floor at its highest, shallow end and slopes down towards the waste. The trough is 500mm deep from that shallow end to the front rim. The second insert level has not been specified.

Which door orientations are available?

H50452(112-1300x0700R) has a right-hand opening door. H50452(112-1300x0700L) has a left-hand opening door. The waste is on the same side as the door in each version.

What is included with the waste outlet?

A 90mm pre-punched waste outlet is provided, with a basket-strainer waste supplied. The trough has a minimum 1:100 fall towards the drain.

What supports dogs at different heights?

Three perforated false-bottom inserts are supplied and can be set at two adjustable levels. The lower level is 850mm above the floor.

Are the hose and trigger spray included?

The hose and trigger spray are excluded from the tub price and are available as optional accessories.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357