PRODUCT RANGE SPECIFICATION

H50452 – Stainless Steel Dog Grooming Tub



PRODUCT IMAGE · Right-hand version shown.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**H50452{PSS}**	**19 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/h50452-stainless-steel-dog-grooming-tub#specifications

01 Product description and specification

Product description

1300 x 700mm Grade 304 stainless steel dog grooming tub with left- or right-hand anti-slip access, three perforated inserts at two levels, basket-strainer waste and three-sided splashbacks.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Dog grooming tub, 1.2mm Grade 304 stainless steel, 1300mm (L) x 700mm (W) x 1600mm overall height. Left- or right-hand door, lower insert at 850mm, 500mm trough depth at the shallow end, 300mm splashbacks, minimum 1:100 fall, 90mm waste outlet with basket-strainer waste, three perforated inserts and 40 x 40mm stainless steel frame with adjustable feet. Hose and trigger spray excluded.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Length	1300	mm	The length of the item typically as measured from left to right.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Width	700	mm	The width of the item typically as measured from front to back.
Height	1600	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Bowl Depth	500	mm	Vertical depth from the highest, shallow end of the trough bottom to the front rim. The bottom slopes down towards the waste.
Splashback Height	300	mm	Vertical height above the front trough rim; the rim is 1300mm above the floor.
Trough Depth Measurement	From the Highest, Shallow End to the Front Rim	–	–
Lower Insert Height	850	mm	Height above the floor of the lower perforated false-bottom insert level.
Trough Bottom Height at Highest Point	800	mm	–
Front Rim Height	1300	mm	–
Framework Material	Stainless Steel Grade 304	–	–
Framework Tube Size	40 x 40 mm	–	–
Feet	Stainless Steel Adjustable Feet	–	–
Splashback Configuration	Rear and Both Sides	–	–
Splashback Top Edge	Safety Hem	–	–
Access Door Type	Foldable Slide-Out Door	–	–
Access Door Surface	Anti-Slip	–	–
Waste Outlet Diameter	90	mm	–
Waste Assembly	Basket-Strainer Waste Supplied	–	–
Waste Outlet Position	Same Side as Access Door	–	–
Minimum Drainage Fall	1:100	–	–
False Bottom Insert Quantity	3	–	–
False Bottom Insert Type	Perforated	–	–
Insert Adjustment Levels	2	–	–
Optional Accessories	Hose and Trigger Spray; Excluded from Tub Price	–	–

03 Configuration options

Door Orientation	Left-Hand; Right-Hand

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 Grade 304 Stainless Steel

1.2mm Grade 304 stainless steel tub with a 40 x 40mm Grade 304 stainless steel tubular frame and stainless steel adjustable feet.

02 Left- or Right-Hand Access

Choose a left- or right-hand opening door. The foldable access door slides out and has an anti-slip surface.

03 Three Adjustable Perforated Inserts

Three perforated false-bottom inserts can be positioned at two levels for different-height dogs. The lower insert level is 850mm above the floor.

04 Door-Side Drainage

A 90mm pre-punched waste outlet and supplied basket-strainer waste are positioned on the same side as the access door for access and maintenance.

05 Fall to Drain

The trough bottom has a minimum 1:100 fall towards the drain. Its highest point is 800mm above the floor.

06 Three-Sided Splashbacks

300mm splashbacks above the trough rim run along the left, right and rear, with a safety hem on the top edge.

05 Application information

Intended applications	Animal Care
Industries	Veterinary Services

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

07 Frequently asked questions

What are the dimensions?

The tub is 1300mm long and 700mm wide. The front rim is 1300mm above the floor and the overall height, including splashbacks, is 1600mm.

How are the trough and insert heights specified?

The lower false-bottom insert is 850mm above the floor. The trough bottom is 800mm above the floor at its highest, shallow end and slopes down towards the waste. The trough is 500mm deep from that shallow end to the front rim. The second insert level has not been specified.

Which door orientations are available?

H50452(112-1300x0700R) has a right-hand opening door. H50452(112-1300x0700L) has a left-hand opening door. The waste is on the same side as the door in each version.

What is included with the waste outlet?

A 90mm pre-punched waste outlet is provided, with a basket-strainer waste supplied. The trough has a minimum 1:100 fall towards the drain.

What supports dogs at different heights?

Three perforated false-bottom inserts are supplied and can be set at two adjustable levels. The lower level is 850mm above the floor.

Are the hose and trigger spray included?

The hose and trigger spray are excluded from the tub price and are available as optional accessories.

E&OE. Specifications are subject to change without notice.