


MODEL SPECIFICATION

H72440(312-1980) – Post Mortem Table Stainless Steel Grade 316 1.2mm Thick 1980mm (L) × 765mm (W) × 900mm (H) with 30mm Recessed Slab, Drainage Fall, Pre-Punched Ø40mm Waste Outlet, Tapered Slab Edge, Reinforced Underbracing, All Welded Construction, Stainless Steel Tubular Frame, Adjustable Feet and Brushed Finish



PRODUCT IMAGE · H72440 post-mortem table; image indicative of the range

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	H72440(312-1980){PSS}	Published catalogue data	4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 316	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Length	1980	mm	The length of the item typically as measured from left to right.
Width	765	mm	Overall table width.
Height	900	mm	Overall table height.
Recessed Slab Depth	30	mm	Depth of the recess in the table top.
Drainage Hole Diameter	40	mm	Diameter of the pre-punched waste opening; this does not specify a supplied waste fitting.
Waste Outlet Hole	Pre-Punched	–	Pre-punched opening for connection to drainage.

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Adjustable Feet	Yes	—	Adjustable foot pieces for levelling during installation.
Framework Material	Stainless Steel	—	Material of the supporting tubular frame.
Framework Profile	Tubular	—	Tubular supporting frame; tube size is not specified.
Construction	All Welded	—	All welded table construction.
Drainage	Drainage Fall	—	The recessed slab falls towards the waste opening.
Finish	Brushed	—	Brushed polish on visible stainless steel surfaces.
Slab Underbracing	Yes	—	Underbracing reinforces the slab.
Slab Edge	Tapered	—	The edge tapers towards the recessed slab.
Mounting Type	Free Standing	—	Freestanding table supported on adjustable feet.

02 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1980	mm
Width	765	mm
Overall height	900	mm

03 Model and supply data

Parent product	H72440 – Stainless Steel Post Mortem Table
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description	The H72440(312-1980) post-mortem table uses Grade 316 stainless steel with a 1.2 mm material thickness. Overall dimensions: 1980 mm (L) × 765 mm (W) × 900 mm (H). 30 mm recessed slab with drainage fall and pre-punched Ø40 mm waste opening. Tapered slab edge and reinforced underbracing. All welded construction, stainless steel tubular frame and adjustable feet. Brushed finish.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield H72440(312-1980) post-mortem table. Grade 316 stainless steel, 1.2 mm material thickness. Overall dimensions: 1980 mm (L) × 765 mm (W) × 900 mm (H). 30 mm recessed slab with drainage fall and pre-punched Ø40 mm waste opening. Tapered slab edge and reinforced underbracing. All welded construction, stainless steel tubular frame and adjustable feet. Brushed finish.

Detailed specification

- Model: H72440(312-1980)
- Material: Stainless Steel Grade 316
- Material thickness: 1.2 mm
- Overall dimensions: 1980 mm (L) × 765 mm (W) × 900 mm (H)
- Recessed slab depth: 30 mm
- Drainage: Fall to a pre-punched Ø40 mm waste opening
- Slab: Tapered edge and reinforced underbracing
- Construction: All welded
- Frame: Stainless steel tubular frame
- Feet: Adjustable for levelling
- Finish: Brushed polish

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.