
MODEL SPECIFICATION

# H72722(315-2400R) – Ventilated Dissection Table Floor Mounted



PRODUCT IMAGE

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | H72722(315-2400R){PSS} | 14 Nov 2026 |

## 01 Model specification

H72722(315-2400R) Ventilated Dissection Table Floor Mounted Stainless Steel Grade 316 2400mm Length with Right-Hand Oriented Bowl

Length: 2400. Basin Orientation: Right. Material: Stainless Steel Grade 316.

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| Length | 2400 | mm | The length of the item typically as measured from left to right. |
| Basin Orientation | Right | – | – |
| Material | Stainless Steel Grade 316 | – | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |

## 03 Model and supply data

| | |
|---|---|
| Parent product | H72722 — Stainless Steel Ventilated Dissection Table Floor Mounted |
| Typical lead time | 10–15 working days |
| Warranty | 12 months |

## 04 Specification notes

**Configuration description**

Floor-mounted stainless steel dissection table with downdraft ventilation for laboratory and examination areas.

Selected configuration: Length: 2400 mm; Basin Orientation: Right; Material: stainless steel Grade 316.

| | |
|---|---|
| **Short Form Specification** | **SPECIFICATION USE**<br>Use this description when specifying this model.<br><br>Basterfield H72722(315-2400R). Floor-mounted stainless steel dissection table with downdraft ventilation for laboratory and examination areas. Selected configuration: Length: 2400 mm; Basin Orientation: Right; Material: stainless steel Grade 316. |
| **Detailed specification** | • Model: H72722(315-2400R)<br>• Length: 2400 mm<br>• Basin Orientation: Right<br>• Material: stainless steel Grade 316 |

## 05 Frequently asked questions

**Which selections identify the required configuration?**

Select Length, Basin Orientation and Material together. Published choices are 1800 mm or 2400 mm, a left-hand or right-hand basin, and Grade 304 or Grade 316 stainless steel.

**What ventilation connection is provided?**

The continuous downdraft grille connects to a 300 mm spigot outlet for external ducting. Coordinate the external ventilation requirements with the installation.

**How is the work area rinsed?**

An integrated sparge rinse system is activated by push-button control. The recessed work area is sloped towards drainage.

**Which additional fittings can be specified?**

Optional additions include perforated trays, macerator units, hands-free mixers and rinse spray assemblies. The tapware landing accommodates medical mixers or other specified fittings.

E&OE. Specifications are subject to change without notice.