
MODEL SPECIFICATION

H72722(315-1800L) – Dissection Table Ventilated 1800mm Length Left



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	H72722(315-1800L){PSS}	14 Nov 2026

01 Model specification

Dissection Table, Grade 316 Stainless Steel, 1800mm Length, with Floor-Mounted Design, Left-Hand Basin, Recessed Draining Work Area, Push-Button Sparge Rinse, Downdraft Grille and 300mm Ducting Spigot, Basterfield H72722(315-1800L)

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1800	mm	The length of the item typically as measured from left to right.
Basin Orientation	Left	–	–
Material	Stainless Steel Grade 316	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Model and supply data

Parent product	H72722 — Stainless Steel Ventilated Dissection Table Floor Mounted
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The H72722(315-1800L) is the 1800mm left-hand basin configuration of the H72722 ventilated dissection table in Grade 316 stainless steel.

The floor-mounted table includes a recessed draining work area, push-button sparge rinse system, continuous downdraft grille, 300 mm spigot outlet for external ducting and a service access panel. Coordinate external ventilation and optional tapware or accessories with the installation.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield H72722(315-1800L) floor-mounted dissection table; Grade 316 stainless steel; 1800mm length; left-hand basin; recessed draining work area; push-button sparge rinse; continuous downdraft grille; 300 mm spigot outlet for external ducting; access panel.

Detailed specification

- Model: H72722(315-1800L)
- Product type: Ventilated dissection table
- Mounting: Floor mounted
- Material: Grade 316 stainless steel
- Length: 1800 mm
- Basin orientation: Left
- Work area: Recessed and sloped towards drainage
- Rinse system: Sparge rinse with push-button control
- Ventilation: Continuous downdraft grille
- Ducting connection: 300 mm spigot outlet
- Service access: Plumbing and ventilation access panel
- Installation: Coordinate external ventilation requirements

05 Frequently asked questions

Which selections identify the required configuration?

Select Length, Basin Orientation and Material together. Published choices are 1800 mm or 2400 mm, a left-hand or right-hand basin, and Grade 304 or Grade 316 stainless steel.

What ventilation connection is provided?

The continuous downdraft grille connects to a 300 mm spigot outlet for external ducting. Coordinate the external ventilation requirements with the installation.

How is the work area rinsed?

An integrated sparge rinse system is activated by push-button control. The recessed work area is sloped towards drainage.

Which additional fittings can be specified?

Optional additions include perforated trays, macerator units, hands-free mixers and rinse spray assemblies. The tapware landing accommodates medical mixers or other specified fittings.

E&OE. Specifications are subject to change without notice.