

PRODUCT RANGE SPECIFICATION

K55688 – Heavy-Duty Stainless Steel Milk Can with Drum-Type Handles



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

K55688{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

25 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.
<https://basterfield.co.za/products/k55688-heavy-duty-stainless-steel-milk-can-with-drum-type-handles#specifications>



01 Product description and specification

Product description

Grade 304 stainless steel milk can with drum-type handles. Choose 15, 20, 25, 30, 40 or 50 L, with optional toggle latch and seal, polished finish and lid connecting chain.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield K55688. Grade 304 stainless steel milk can with drum-type handles, fitted lid, smooth-ground welds and reinforcing base rim. Capacity: 15, 20, 25, 30, 40 or 50 L. Satin-brushed finish as standard. Optional toggle latch and seal, polished mirror finish and lid connecting chain, in any combination.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Handle Type	Drum Handles	—	The carrying handle construction fitted to this milk-can product.

03 Configuration options

Capacity

15 L; 20 L; 25 L; 30 L; 40 L; 50 L

Toggle Latch and Seal Upgrade	No; Yes
Finish	Polished Mirror Finish; Satin Brushed Finish
Connecting Chain	No; Yes

Options vary by model; not every combination is available. Use the product page to select a model.

04 Application information

Intended applications	Liquid Storage & Handling
Industries	Dairy & Beverage Processing

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.